


LT PR 36/IR890

PATTERN PROJECTOR,
IR @ 890 NM



Part Number		LTPR36/IR890
Light Color, wavelength peak		IR, 890 nm
DEVICE POWER RATINGS		
Minimum DC Voltage	(volt)	12
Maximum DC Voltage	(volt)	24
Power Consumption	(watt)	< 2
LED DIRECT DRIVE RATINGS		
Forward DC Voltage	(volt)	1,6
Forward Current	(mA)	500
Pulse Ratings @0,1 duty/1kHz	(mA)	n.a.



MECHANICAL DRAWINGS: see next page >>

Rev No.	Description	Date	Name
A	Nuovo pezzo	05/12/07	A.Vismara



Material	N.A.			Mass	163.8 g	Scale	2:1
Surface treatment	N.A.			Project-Prod.Item/Instrument		LTSPPR	
Geometrical tolerance (ISO 2768-2)			Class	K	Undimensioned bevels	1x45°	Description
Linear tolerance (ISO 2768-2)			Class	m			
0.5	>3-	>6-	>30+	>120	>400+	>1000	>2000
-3	6	30	120	+400	1000	+2000	+4000
±0.1	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2
www.opto-engineering.com			Date	Name	Drawing No.		Sheet
			Designed	17/03/03	A.Vismara	03532-0-A	1/1
			Draw	05/12/07	A.Vismara		
			Checked	X	C. Sedazzari		
OPTO ENGINEERING S.r.l. - 46100 Mantova Italy - Via Cremona, 29/2 - Tel. +39 0376 229585 - e-mai: info@opto-engineering.it - http://www.opto-engineering.com							

Description
LAYOUT WITH C-MOUNT

Reproduction forbidden without specific authorization