


LT PR 36/UV385

PATTERN PROJECTOR,
UV @ 385 NM



Part Number		LTPR36/UV385
Light Color, wavelength peak		UV, 385 nm
DEVICE POWER RATINGS		
Minimum DC Voltage	(volt)	12
Maximum DC Voltage	(volt)	24
Power Consumption	(watt)	< 2
LED DIRECT DRIVE RATINGS		
Forward DC Voltage	(volt)	3,7
Forward Current	(mA)	350
Pulse Ratings @0,1 duty/1kHz	(mA)	n.a.



MECHANICAL DRAWINGS: see next page >>

Rev No.	Description	Date	Name
A	Nuovo pezzo	05/12/07	A.Vismara



Material	N.A.			Mass	163.8 g	Scale	2:1	
Surface treatment	N.A.			Project-Prod.Item/Instrument	LTSPPR			
Geometrical tolerance (ISO 2768-2)			Class	K	Undimensioned bevels	1x45°	Description	
Linear tolerance (ISO 2768-2)			Class	m				Undimensioned radii
0.5 +3	>3- 6	>6- 30	>30- 120	>120 +400	>400- 1000	>1000 +2000	>2000 +4000	
±0.1	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2	
www.opto-engineering.com			Date		Name		Drawing No.	
			Designed		A.Vismara		03532-0-A	
			Draw		A.Vismara			
			Checked		C. Sedazzari			
OPTO ENGINEERING S.r.l. - 46100 Mantova Italy - Via Cremona, 29/2 - Tel. +39 0376 229585 - e-mai: info@opto-engineering.it - http://www.opto-engineering.com			Date		Name		Sheet	
			17/03/03		A.Vismara		1/1	
			05/12/07		A.Vismara			
			X		C. Sedazzari			
<i>Reproduction forbidden without specific authorization</i>								