



RT-LSW-15-070-3-POL

Polarizer for LSW-15-070-3

SPECIFICATIONS

Mechanical specifications

Thickness	(mm)	0.8
-----------	------	-----

Compatibility

Compatible products	RT-LSW-15-070-3-W-24V-FL, RT-LSW-15-070-3-R-24V-FL RT-LSW-15-070-3-G-24V-FL, RT-LSW-15-070-3-B-24V-FL
---------------------	--

COMPATIBLE PRODUCTS

LTRNDC series

Continuous LED direct ringlights

RT-LSW-15-070-3-W-24V-FL	Continuous LED direct ringlight, inner diameter 32 mm, 15°, white, RT-EXT-24V-F-3M 3 meters cable included.
RT-LSW-15-070-3-R-24V-FL	Continuous LED direct ringlight, inner diameter 32 mm, 15°, red, RT-EXT-24V-F-3M 3 meters cable included.
RT-LSW-15-070-3-G-24V-FL	Continuous LED direct ringlight, inner diameter 32 mm, 15°, green, RT-EXT-24V-F-3M 3 meters cable included.
RT-LSW-15-070-3-B-24V-FL	Continuous LED direct ringlight, inner diameter 32 mm, 15°, blue, RT-EXT-24V-F-3M 3 meters cable included.

